

SCG DATA SHEET

SADIE E & JEWEL C



A TIMELESS ROOF FOR A BETTER TOMORROW



Description

Sadie E and Jewel C are slurry-coated concrete roof tiles with an interlocking profile. Featuring Double Coating Technology with a two-layer colour coating, they offer enduring aesthetics and reliable long-term performance

Key Technology & Features



DOUBLE COATING TECHNOLOGY



RELIABLE COLOUR PERFORMANCE



INTERLOCKING PROFILE

Technical Data

Thai Industrial Standard
Tile coverage (+/- 2%)

Dimensions (+/- 2%)

Effective tile width after overlap
Weight (+/- 2%)

Head lap adjustment (mm)
Design load of tiles per sq.m.
Roof pitch



TIS 535-2556
Approx. 9.80 tiles/m²
at 34 cm batten spacing
10.42 tiles/m² at 32 cm
batten spacing
Length: 420 mm
Width: 330 mm
300 mm
Per tile: 4.05 kg
Approx. 39.7 kg/m²
at 34 cm spacing, 42.2 kg/m²
at 32 cm spacing
80-100
45 kg/m²
Minimum 17°
Recommended 30-35°
Maximum 90°



SADIE E



JEWEL C



Color of Product

Available



Onyx Black



Seagull Grey



Lignite Grey



Golden Brown



Titanium



Cotton White

Made-to-Order



Dark Grey



Tantalum Grey



Brown Oak